

1. PRODUCT NAME

LATICRETE EPISTRIP A

2. MANUFACTURER

LATICRETE Pty Ltd.

464 Geelong Road,
Footscray West. VIC. 3012.

Telephone: 03 99336111

Toll Free: 1800 331012

Fax: 03 99336199

Email: laticreteoz@laticrete.com.au**3. PRODUCT DESCRIPTION**

LATICRETE EPISTRIP A is specially formulated to remove epoxy grout film from tile and stone surfaces.

4. SAMPLE TESTING.

Due to the differences of the types of material to be cleaned, several inconspicuous test patches should be completed to test compatibility and assure maximum performance. **User must determine suitability of the product for their intended use.**

5. PROTECTION.

Always protect neighboring surfaces including wood, carpet, metals, landscaping and other surfaces.

6. HOW TO USE.

Once floors have been cleaned with LATICRETE TC2000 and all dirt has been removed, use LATICRETE EPISTRIP A for the cleaning and removing of any epoxy residue and haze. For best results under normal circumstances such as cleaning down floor and wall tiles etc, use Epistrip undiluted. Allow Epistrip A to penetrate the surface. This may take from 60 seconds to several hours depending on the depth of the epoxy to be removed. Wash all treated areas with water to remove final traces of Epistrip A. LATICRETE Epistrip A can also be used as a general final clean for tiles and stone, a dilution rate of 1:1 with hot water will give best results.

Packaging – 1 litre jugs.

Shelf Life – Factory sealed containers of this product are guaranteed to be of first quality for one (1) years if stored at temperatures >4°C and <43°C.

Limitations

- This product must not be mixed with other soaps, detergents, or disinfectants, as this will greatly diminish its working capacity.

Caution

- Use in a well ventilated area. Provide adequate ventilation in closed or confined areas. Skin and eye irritant. Avoid prolonged contact with skin. Avoid prolonged contact exposure to vapors. Do not take internally. Keep small children and

- pets out of area until product or surface has thoroughly dried.
- Gloves and suitable eye protection should be worn at all times.
- Keep out of reach of children.
- LATICRETE TC2000 Liquid is alkaline, use PVC gloves, eye protection and protective clothing.
- See Material Safety Data Sheets for more information.

7. WARRANTY

Instructions are a condensed guide and should not be considered to be complete. In the event of a failure, the only obligation of LATICRETE shall be to replace such product proven to be defective. Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein. Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

8. TECHNICAL SERVICES

Technical assistance and information is available by calling the LATICRETE Technical Service Line:

Toll Free 1800331012 or 03 99336111

Fax 03 99336199

Call Laticrete for up to date technical data sheets, material safety data sheets and how to brochures.