



## LATICRETE SHOCK CLEAN HIGH PERFORMANCE CLEANER

Data Sheet Shockcleanaus.0

### 1. PRODUCT NAME

LATICRETE SHOCK CLEAN

### 2. MANUFACTURER

LATICRETE Pty Ltd.

464 Geelong Road,

Footscray West. VIC. 3012.

Telephone: 03 9933 6111

Toll Free: 1800 331012

Fax: 03 9933 6199

Email: [laticreteoz@laticrete.com.au](mailto:laticreteoz@laticrete.com.au)

### 3. PRODUCT DESCRIPTION

LATICRETE SHOCK CLEAN is a specially formulated, extremely high performance cleaner. This product is formulated to clean commercial and industrial porcelain and vitrified floor tiles. Ensure you follow the instructions.

### 4. SAMPLE TESTING.

Due to the differences of each material, several inconspicuous test patches should be completed to test compatibility and assure maximum performance. Ensure that SHOCK CLEAN is not etching or damaging the face of the tile. **User must determine suitability of the product for their intended use.**

### 5. PROTECTION AND SAFETY.

LATICRETE SHOCK CLEAN is a powerful acid mixture which is potentially corrosive to skin and soft tissue. Appropriate safety equipment **MUST** be worn when handling this product. Adequate precautions should be taken to ensure that unprotected workers and the public are not exposed to spray, mist or run off during the cleaning process. Laticrete Pty Ltd will not be held responsible for any mishap that occurs with the use of this product. For further information, refer to the material safety data sheet for this product.

**CAUTION:** This product should not be allowed to come into contact with aluminum, zinc, tin or unprotected metal surfaces. This product may etch glass if allowed to dry on a glass surface. **DO NOT STORE OR USE IN METAL CONTAINERS.**

Always protect people and neighboring surfaces including wood, carpet, metals, landscaping and other surfaces and the like.

### 6. HOW TO USE.

Ensure the tiled surface to be clean is free from any dust/dirt or grit prior to treatment. Wet down surface to be cleaned with water and saturate grout joints. After grout joints are saturated, remove any free standing water. Then apply the product directly to the surface. Treat small areas, less than 5m<sup>2</sup> at a time and ensure product is not in contact with the tiles for more than 5 minutes. Allow the product to sit in contact with the surface for 2 minutes then scrub surface with a stiff broom. Allow product to sit for a further 2 minutes before removing with clean water. Ensure product has been entirely removed from the cleaned surface. Flush

cleaned areas with copious amounts of clean water. Repeat process until entire surface has been cleaned. Product runoff should be neutralized with either Laticrete Neutralizer, sodium bicarbonate or sodium carbonate (dense soda ash) prior to disposal.

### Packaging & Coverage – 1 litre bottle and 20 litre pail.

Product coverage should be approximately 10m<sup>2</sup> per litre. Shock clean can be diluted with clean water.

**Shelf Life** – Factory sealed containers of this product are guaranteed to be of first quality for one (1) years if stored at temperatures >4°C and <43°C.

### Disclaimer

- The use of this product is out of the control of Laticrete Pty Ltd or the retail suppliers of this product and Laticrete Pty Ltd and the retail suppliers of this product are not responsible for any damages resulting for the use of this product.

### Caution

- Use in a well ventilated area. Provide adequate ventilation in closed or confined areas. Respirators of the selected class and type will depend upon the level of breathing zone contamination.
- As a minimum: skin and eye protection must be worn. Avoid contact with skin. Avoid prolonged contact exposure to vapors. Do not take internally. Wear safety goggles or full face shield, suitable overalls, impervious rubber gloves and boots.
- Keep small children and pets out of area until product has been neutralized.
- Keep out of reach of children.
- Dispose of shock clean or neutralized shock clean as per the EPA guidelines, state and federal laws.
- See Material Safety Data Sheets for more information.

### 7. WARRANTY

Instructions are a condensed guide and should not be considered to be complete. In the event of a failure, the only obligation of LATICRETE shall be to replace such product proven to be defective. Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.

### 8. TECHNICAL SERVICES

Technical assistance and information is available by calling the LATICRETE Technical Service Line:

Toll Free 1800331012 or 03 9933 6111

Fax 03 9933 6199