



LATEX CEMENT COATINGS OVER ASPHALT PAVEMENT TDS 121

LATICRETE[®] 3701 Mortar Admix and LATICRETE 8510 Bonding Admix with Portland cement/sand mixes, such as LATICRETE Tri-Poly Fortified Sanded Grouts (1500 Series), have been used successfully for many years to apply thin paint and heavier traffic coatings over existing asphalt pavement.

TENNIS COURTS:

Asphalt tennis courts can be re-coated or color coated using LATICRETE Tri-Poly Fortified Sanded Grout (1500 Series) mixed with LATICRETE 3701 Mortar Admix or LATICRETE 8510 Bonding Admix and applied by roller or brush to provide new decorative colored surface. Application thickness by roller or brush will be approximately 1/16" (1.5mm) thick.

Trowel applied coatings can also be made using LATICRETE Tri-Poly Fortified Sanded Grout (1500 Series) with LATICRETE 3701 Mortar Admix or LATICRETE 8510 Bonding Admix and applied 1/8" to 3/16" (3mm to 4.5mm) thickness. LATICRETE Tri-Poly Fortified Sanded Grout (1500 Series) will provide attractive, decorative and extremely serviceable coatings that adhere to existing asphalt tennis courts or pavements.

TRAFFIC COATINGS:

Applied from 1/4" to 3/8" (6mm to 9mm) thickness can be made using LATICRETE 226 Thick Bed Mortar mixed with LATICRETE 8510 Bonding Admix. These coatings can be colored or tinted to provide decorative traffic surfaces that will take wheeled traffic.

CAUTION:

Asphalt pavements that are to be covered must be sufficiently weathered to remove all free oils, clean and free from deterioration. Where automobiles have dripped oil or gasoline, asphalt pavement may have permanently been damaged; leaving sticky or tacky surfaces that will not provide long lasting installations. Pre-treat those areas with LATAPOXY[®] 210 Modified Epoxy Adhesive before application of traffic coating. Length of service may be limited if there is oil or grease has damaged the asphalt.

HISTORY:

LATICRETE Latex Cement Coatings have been used for many years and provide long lasting weatherproof service even in northern climates.

NOTE: Avoid dark colored cement coatings that may show shading when dry.

Technical Data Sheets are subject to change without notice. For latest revision, check our website @ www.laticrete.com

TDS 121.doc R 3 January 2005

LATICRETE, LATAPOXY and the  logo are Registered Trademarks of LATICRETE International, Inc.



LATICRETE INTERNATIONAL, INC. • 1 LATICRETE Park North, Bethany, Ct 06524-3423
Tel: (203) 393-0010 • (800) 243-4788 • Fax: (203) 393-1684 • www.laticrete.com • support@laticrete.com