



**S.I. CONVERSIONS FOR
LBS./IN.² & KG/CM²
TDS 125**

$$\begin{aligned} 1\text{N/mm}^2 &= 1\text{MPa} \\ &= 145.038\text{ lbs./in.}^2 \\ &= 10.156\text{ kg/cm}^2 \end{aligned}$$

$$\begin{aligned} 145.038\text{ lbs./in.}^2 &= 1\text{MPa} \\ &= 1\text{N/mm}^2 \\ &= 10.156\text{ kg/cm}^2 \end{aligned}$$

$$\begin{aligned} \text{lbs./in.}^2 \text{ divided by } 145.038 &= \text{N/mm}^2 \\ &= \text{MPa} \end{aligned}$$

$$\text{N/mm}^2 \times 145.038 = \text{lbs./in.}^2$$

$$\text{kg/cm}^2 \text{ divided by } 10.156 = \text{N/mm}^2$$

$$\text{kg/cm}^2 \times 14.28 = \text{lbs./in.}^2$$

Technical Data Sheets are subject to change without notice. For latest revision, check our website @ www.laticrete.com
TDS 125.doc R 3 January 2005

LATICRETE, LATAPOXY and the  logo are Registered Trademarks of LATICRETE International, Inc.

