



LATICRETE® 10 Year System Warranty

Data Sheet 230.12

LIMITED WARRANTY

Subject to the conditions and limitations stated below, LATICRETE® INTERNATIONAL, INC. ("LATICRETE") warrants that the products listed on this document will be free from manufacturing defects and will not break down or deteriorate under normal usage for a period of ten (10) years from the date of purchase when installed in accordance with LATICRETE's written specifications and industry standard guidelines. For this limited warranty to apply, the applications that comprise the installation must be performed with the products listed in this document for each application (refer to chart).

DISCLAIMER

THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED. THERE ARE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE OF THIS DOCUMENT. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED.

EXCLUSIVE REMEDY

The sole and exclusive remedy for a breach of this limited warranty is replacement of only the specific portion of the installation that is proven to be defective*. LATICRETE will pay for replacement of its own products and replacement of finishing materials, as well as for labor for the replacement installation, but LATICRETE will not pay more, calculated on a square-foot basis, for the replacement than the original purchase price of the portion being replaced. LATICRETE will not pay for replacement of any portion of the installation that is not proven to be defective.

In the event that the sole and exclusive remedy described above fails of its essential purpose, LATICRETE's liability is limited to the dollar value, on a square-foot basis, of the original purchase price of the portion being replaced. Notwithstanding the previous paragraphs, exterior facades with ceramic tile or stone installed over substrates with steel or wood framing **do not qualify** for this limited warranty – see Data Sheet 230.15 for such applications.

EXCLUSIONS

LATICRETE is not responsible for workmanship not in accordance with LATICRETE's instructions and industry standard guidelines. Cracking due to structural movement, excessive deflection or other failure in the substrate is also not covered.

LATICRETE IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.

*NOTE: Efflorescence is a normal condition of portland cement mortars and is not a defective condition.

NO ASSIGNMENT

This limited warranty is not transferable or assignable

HOW TO MAKE A CLAIM

To make a claim under this limited warranty, you must notify LATICRETE in writing within thirty (30) days of the discovery of the alleged manufacturing defect. At LATICRETE's option, you may be required, as a condition of this limited warranty, to provide proof of product purchase and use.

Address your claim to:

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA
Attn: Technical Service Department

TECHNICAL INFORMATION

Technical assistance and information is available by calling the LATICRETE Technical Service Line:

Toll Free: (800) 243-4788, ext. 235 or (203) 393-0010, ext. 235.

Fax: (203) 393-1948.

APPLICATION	PRODUCTS
Underlayment	LATICRETE 86 Latilevel Self Leveling Underlayment LATICRETE Admix and Primer for Underlayments
Waterproofing Membrane	LATICRETE 9235 Waterproofing Membrane LATAPOXY® 24hr HydroProofing
Sound Control	LATICRETE 18 Sound Control Underlayment
Anti-Fracture Membrane	LATICRETE Blue 92 Anti-Fracture Membrane
Plaza & Deck	LATICRETE Plaza & Deck System
Thick bed method	LATICRETE 3701 Mortar Admix mixed with LATICRETE 226 Thick Bed Mortar
Slurry Bond Coat	<ul style="list-style-type: none"> LATICRETE 254 Platinum Multipurpose Thin-Set Mortar OR LATICRETE 4237 Latex Thin-Set Mortar Additive mixed with LATICRETE 211 Crete Filler Powder OR LATICRETE 3701 Mortar Admix with LATICRETE 211 Crete Filler Powder (for use under Mortar Beds only)
Thin bed method	<ul style="list-style-type: none"> LATICRETE 254 Platinum Multipurpose Thin-Set Mortar LATICRETE 4237 Latex Thin-Set Mortar Additive mixed with any of the following: LATICRETE 211 Crete Filler Powder OR LATICRETE 272 Premium Floor N' Wall Thin-Set Mortar OR LATICRETE 317 Floor N' Wall Thin-Set Mortar LATICRETE 3701 Mortar Admix mixed with any of the following: LATICRETE 272 Premium Floor N' Wall Thin-Set Mortar OR LATICRETE 317 Floor N' Wall Thin-Set Mortar OR LATICRETE 220 Marble & Granite Mortar LATICRETE 333 Super Flexible Additive mixed with any of the following: LATICRETE 272 Premium Floor N' Wall Thin-Set Mortar OR LATICRETE 317 Floor N' Wall Thin-Set Mortar OR LATICRETE 220 Marble & Granite Mortar (Exterior use limited to Residential/Light Commercial applications. Do not use in areas not subject to water immersion) LATICRETE 255 MultiMax Multipurpose Thin-Set Mortar (US 6,784,229 B2) LATAPOXY® 300 Epoxy Adhesive
Spot Bonding	<ul style="list-style-type: none"> LATAPOXY 310 Stone Adhesive-Standard and Rapid Grade
Grouting	<ul style="list-style-type: none"> LATICRETE SpectraLOCK™ PRO Grout (patent pending) (non-industrial applications) LATAPOXY SP-100 Stainless Grout for Floors N' Walls (non-industrial applications) LATAPOXY 2000 Industrial Epoxy Grout LATICRETE 1776 Grout Admix Plus mixed with either of the following: LATICRETE Tri-Poly Fortified Sanded Grout (1500 Series) OR LATICRETE Tri-Poly Fortified Unsanded Grout (1600 Series)
Sealant†	<ul style="list-style-type: none"> LATICRETE Latasil Tile & Stone Sealant LATICRETE Latasil 9106 Stone Primer LATICRETE Latasil 9108 Swimming Pool Primer

†Use of suitable flexible sealant is required per Tile Council of America Detail EJ171 for use in expansion joints, coves, corners, changes in plane and other joints or wherever tile or stone abuts dissimilar materials or restraining surfaces.



**Globally proven.
Professionally endorsed.**

LATICRETE INTERNATIONAL, INC.

1 LATICRETE PARK NORTH • BETHANY, CT 06524-3423 USA
TEL: (203) 393-0010 • (800) 243-4788 • FAX: (203) 393-1084
www.laticrete.com • support@laticrete.com

Middle East: (971) (7) 244-5096 • China: (86) (21) 6497-2045
Asia Pacific: (652) 2528-8580 • Europe: (34) (93) 649-1909
Latin America: (1) (202) 331-0010 • India: (91) (40) 2367-3775

©2015 LATICRETE INTERNATIONAL, INC.
LATICRETE, LATAPOXY and the LATICRETE logo are Registered Trademarks of LATICRETE International, Inc.