



LATICRETE® Lifetime Residential Warranty

Data Sheet 700.12

LIMITED WARRANTY

Subject to the conditions and limitations stated below, LATICRETE INTERNATIONAL, INC. ("LATICRETE") warrants that the products listed on this document will be free from manufacturing defects and will not break down or deteriorate under normal usage for the life of the residence when installed in accordance with LATICRETE'S written specifications and industry standard guidelines. For this limited warranty to apply, the applications that comprise the installation must be performed with the products listed in this document for each applicant (refer to chart).

DISCLAIMER

THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESSED OR IMPLIED. THERE ARE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE OF THIS DOCUMENT. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED.

EXCLUSIVE REMEDY

As the sole and exclusive remedy for a breach of this limited warranty, LATICRETE will pay for the replacement of its own products and replacement of finishing materials, as well as for the replacement installation, but LATICRETE will not pay more for the replacement, calculated on a square-foot basis, than the original purchase price of the portion being replaced. LATICRETE will not pay for replacement of any portion of the installation that is not proven to be defective.

In the event that the sole and exclusive remedy described above fails of its essential purpose, LATICRETE's liability is limited to the dollar value, on a square-foot basis, of the original purchase price of the portion being replaced. Notwithstanding the previous paragraphs, exterior facades with ceramic tile or stone installed over substrates with steel or wood framing **do not qualify** for this limited warranty – see Data Sheet 230.15 for such applications.

EXCLUSIONS

LATICRETE is not responsible for workmanship not in accordance with LATICRETE'S instructions and industry standard guidelines. Cracking due to structural movement, excessive deflection or other failure in the substrate is also not covered.

LATICRETE IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.

*NOTE: Efflorescence is a normal condition of portland cement mortars and is not a defective condition.

NO ASSIGNMENT

This limited warranty is not transferable or assignable

HOW TO MAKE A CLAIM

To make a claim under this limited warranty, you must notify LATICRETE in writing within thirty (30) days of the discovery of the alleged manufacturing defect. At LATICRETE'S option, you may be required, as a condition of this limited warranty, to provide proof of product purchase and use.

Address your claim to:

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA
Attn: Technical Service Department

TECHNICAL INFORMATION

Technical assistance and information is available by calling the LATICRETE Technical Service Line:
Toll Free: (800) 243-4788, ext. 235 or (203) 393-0010, ext. 235.
Fax: (203) 393-1948.

APPLICATION	PRODUCTS
Underlayment	LATICRETE 86 Latilevel Self Leveling Underlayment LATICRETE Admix and Primer for Underlayments
Waterproofing	Continuous submersion or shower pan: <ul style="list-style-type: none"> LATICRETE® 9235 Waterproofing Membrane Intermittent wet areas, or as secondary membrane in shower: <ul style="list-style-type: none"> LATICRETE Watertight Floor N' Wall Waterproofing LATICRETE 9235 Waterproofing Membrane
Anti-Fracture	<ul style="list-style-type: none"> LATICRETE BLUE 92 Anti-Fracture Membrane (Full Floor Coverage) LATICRETE Crack Suppression Kit (treat only existing cracks)
Thin Bed Method	<ul style="list-style-type: none"> LATICRETE 254 Platinum Multipurpose Thin-Set Mortar LATICRETE 333 Super Flexible Additive mixed with any of the following: LATICRETE 272 Premium Floor N' Wall Thin-Set Mortar <u>OR</u> LATICRETE 317 Floor N' Wall Thin-Set Mortar <u>OR</u> LATICRETE 220 Marble & Granite Mortar (Do not use in areas subject to water immersion) LATICRETE 255 MultiMax Multipurpose Thin-Set Mortar (US 6,784,229 B2) LATAPOXY® 300 Epoxy Adhesive
Grout	<ul style="list-style-type: none"> LATICRETE SpectraLOCK™ PRO Grout (patent pending)
Sealant†	<ul style="list-style-type: none"> LATICRETE Latasil Tile & Stone Sealant LATICRETE Latasil 9106 Stone Primer LATICRETE Latasil 9108 Swimming Pool Primer

†Use of suitable flexible sealant is required per Tile Council of America Detail EJ171 for use in expansion joints, coves, corners, changes in plane and other joints or wherever tile or stone abuts dissimilar materials or restraining surfaces.



**Globally proven.
Professionally endorsed.**

LATICRETE INTERNATIONAL, INC.

1 LATICRETE PARK NORTH • BETHANY, CT 06524-3423 USA
TEL: (203) 393-0010 • (800) 243-4788 • FAX: (203) 393-1084
www.laticrete.com • support@laticrete.com

Middle East: (971) (7) 244-5096 • China: (86) (21) 6497-2045

Asia Pacific: (652) 2528-6660 • Europe: (34) (96) 649-1909

Latin America: (1) (202) 333-0010 • India: (91) (40) 2367-3775

©2015 LATICRETE INTERNATIONAL, INC.
LATICRETE, LATAPOXY and the logo are Registered Trademarks of LATICRETE International, Inc.